



“

TRUCK SPREADERS & ACCESSORIES

MORE JOBS.
DONE FASTER.





“



SPREADER SERIES
TAILGATE SERIES
WALK-BEHIND / STORAGE
ACCESSORIES / SPECS



RISE TO NEW CHALLENGES

WHETHER OR NOT THEY HAPPEN DURING REGULAR BUSINESS HOURS

When snow and ice control is your profession, it's up to you to keep the world moving through winter's worst. Less time worrying about your equipment means more time keeping your lots free of snow and ice.

The ticking clock controls your paycheck. Minutes wasted are dollars lost. When your schedule is packed and your budget even tighter, the only thing worth your hard-earned money is *better results*.

That's why Western Products builds efficiency into every feature of our spreaders and plows. With over 75 years of experience behind us, Western Products knows what it takes to conquer all the depths of winter.

Mother Nature may not offer guarantees—but we build a promise into every piece of equipment we make:

MORE JOBS. DONE FASTER.

PURPOSE-BUILT FOR YOUR OPERATION

When the temperature drops and ice threatens, be prepared with the right tool for the job. Western Products offers a full line of ice control equipment and accessories to ensure your operation has the best solution for your vehicle fleet and the properties you service.



HOPPERS

If you provide large properties with de-icing services and have access to bulk de-icing materials, a hopper spreader is the option for you.

VEHICLE APPLICATION

Hopper spreaders are compatible with half-ton up to Class 6 work trucks.

DE-ICING MATERIAL

Choose the right tool for the job with the HELIXX™ auger optimized for spreading rock salt, or a pintle chain conveyor for dense materials like sand or salt & sand mix.

HOPPER CONSTRUCTION

Choose either rugged stainless steel or durable, lightweight polyethylene.

TAILGATES

If you're providing de-icing services to small, congested properties or outfitting your supervisor trucks, a tailgate spreader is the option for you.

DE-ICING MATERIAL

Tailgates are best for spreading bagged de-icing materials like rock salt and calcium chloride.

VEHICLE APPLICATIONS

Treat congested and compact areas with tailgate spreaders on 1-ton or smaller pickups with a variety of mounting options.

SPREAD PATTERN

The broadcast spread pattern distributes de-icing materials evenly with a variety of widths to match the application..





HOPPER SERIES

FEATURING THE **MARAUDER™** SPREADERS

“ RIGHT TOOL FOR THE JOB.

When icy conditions are in the forecast, you need to go on the offensive to keep your properties safe. The MARAUDER™ line of hopper spreaders offers a wide variety of sizes and material delivery systems to hunt down and prevent ice formation. A hopper spreader from WESTERN® is the right choice for large, open properties when you treat with bulk rock salt.



MATERIAL DELIVERY SYSTEM

Choose the best material delivery system for your operation based on the de-icer you commonly use—either the all-new HELIXX™ shaftless auger for precise rock salt application or the pintle chain conveyor that's perfect for thick, heavy de-icing materials like sand and salt/sand mix. Whatever choice you make, you'll get the delivery performance you demand.



HOPPER GEOMETRY

The hopper tub geometry is designed to optimize material flow. This allows for a smoother, even flow that prevents materials from getting stuck or bridging.



HOPPER CONSTRUCTION

Stainless steel or polyethylene construction allows you to choose the material that best suits your vehicle fleet.



STANDARD LIDS

The polyethylene models come standard with lids featuring molded channels for moisture run off. Pockets at the end of the lid allow a 2x4 or shovel to be inserted for leverage while opening and closing.

MARAUDER™

STAINLESS STEEL HOPPER SPREADERS



0.35 | 0.7 CU YD

S035C | S035A | S070C | S070A

1.5 CU YD

S150C | S150A

2.2 CU YD

S220C | S220A

FEATURES	DESCRIPTION	FEATURES	DESCRIPTION	FEATURES	DESCRIPTION
CAPACITY	0.35 cu yd 0.7 cu yd	CAPACITY	1.5 cu yd	CAPACITY	2.2 cu yd
CAPACITY WITH EXTENSION COLLAR*	0.6 cu yd 1.2 cu yd	CAPACITY WITH EXTENSION COLLAR*	2.0 cu yd	CAPACITY WITH EXTENSION COLLAR*	2.7 cu yd
CONSTRUCTION	Stainless Steel	CONSTRUCTION	Stainless Steel	CONSTRUCTION	Stainless Steel
MATERIAL DELIVERY SYSTEM	HELIXX™ Auger Technology features a patented corkscrew material delivery system that is optimized to operate in the target range for rock salt spreading best practices. Pintle Chain Conveyor delivers reliable, smooth, and consistent material flow for heavy, dense materials while reducing bridging.	MATERIAL DELIVERY SYSTEM	HELIXX Auger Technology features a patented corkscrew material delivery system that is optimized to operate in the target range for rock salt spreading best practices. Pintle Chain Conveyor delivers reliable, smooth, and consistent material flow for heavy, dense materials while reducing bridging.	MATERIAL DELIVERY SYSTEM	HELIXX Auger Technology features a patented corkscrew material delivery system that is optimized to operate in the target range for rock salt spreading best practices. Pintle Chain Conveyor delivers reliable, smooth, and consistent material flow for heavy, dense materials while reducing bridging.
ACCESSORIES	Tri-Shield Pre-Wet & Liquid Application System (S070), Rearview Material Monitoring Camera, Extension Collars, Spill Guard, Ratchet Tie-Down Kit, Central Point Grease Kit (S070C only), Vibrator, Inverted V, License Plate Kit, LED Strobe Light Kit, LED Work Light Kit, Pullover Tarp Kit, Vehicle Side Harness Kit, Truck Upfit Kit (S035), License Plate Kit (S035)	ACCESSORIES	Tri-Shield Pre-Wet & Liquid Application System, Rearview Material Monitoring Camera, Extension Collars, Spill Guard Kit, Central Point Grease Kit (S150C only), Pullover Tarp Kit, Ratchet Tie-Down Kit, Chain Tie-Down Kit, Vibrator, Inverted V (Accessory for S150C, standard on S150A), LED Work Light Kit, LED Strobe Light Kit, Feed Gate (S150C)	ACCESSORIES	Tri-Shield Pre-Wet & Liquid Application System, Rearview Material Monitoring Camera, Extension Collars, Spill Guard Kit, Central Point Grease Kit (S150C only), Pullover Tarp Kit, Ratchet Tie-Down Kit, Chain Tie-Down Kit, Vibrator, Inverted V (Accessory for S150C, standard on S150A), LED Work Light Kit, LED Strobe Light Kit, Feed Gate (S220)
VEHICLE COMPATIBILITY	UTVs (S035C/S035A); ½, ¾ or 1-Ton Pickup Truck**	VEHICLE COMPATIBILITY	¾- & 1-Ton Pickup Trucks	VEHICLE COMPATIBILITY	¾- & 1-Ton Pickup Trucks
MIN. RECOMMENDED BED LENGTH	30" (S035C/S035A) 44" (S070C/S070A)	MIN. RECOMMENDED BED LENGTH	76"	MIN. RECOMMENDED BED LENGTH	90"



3.0 CU YD

S300C | S300A

4.0 CU YD

S400C | S400A

5.0 CU YD

S500C | S500A

FEATURES	DESCRIPTION	FEATURES	DESCRIPTION	FEATURES	5.0 cu yd
CAPACITY	3.0 cu yd	CAPACITY	4.0 cu yd	CAPACITY	5.0 cu yd
CAPACITY WITH EXTENSION COLLAR*	4.0 cu yd	CAPACITY WITH EXTENSION COLLAR*	5.0 cu yd	CAPACITY WITH EXTENSION COLLAR*	6.0 cu yd
CONSTRUCTION	Stainless Steel	CONSTRUCTION	Stainless Steel	CONSTRUCTION	Stainless Steel
MATERIAL DELIVERY SYSTEM	HELIXX™ Auger Technology features a patented corkscrew material delivery system that is optimized to operate in the target range for rock salt spreading best practices. Pintle Chain Conveyor delivers reliable, smooth, and consistent material flow for heavy, dense materials while reducing bridging.	MATERIAL DELIVERY SYSTEM	HELIXX Auger Technology features a patented corkscrew material delivery system that is optimized to operate in the target range for rock salt spreading best practices. Pintle Chain Conveyor delivers reliable, smooth, and consistent material flow for heavy, dense materials while reducing bridging.	MATERIAL DELIVERY SYSTEM	HELIXX Auger Technology features a patented corkscrew material delivery system that is optimized to operate in the target range for rock salt spreading best practices. Pintle Chain Conveyor delivers reliable, smooth, and consistent material flow for heavy, dense materials while reducing bridging.
ACCESSORIES	Tri-Shield Pre-Wet & Liquid Application System, Rearview Material Monitoring Camera, Extension Collars, Spill Guard Kit, Central Point Grease Kit (S300C only), Ratchet Tie-Down Kit, Chain Tie-Down Kit, Vibrator, LED Work Light Kit, LED Strobe Light Kit, Rolled Tarp Kit, Feed Gate (S300C)	ACCESSORIES	Tri-Shield Pre-Wet & Liquid Application System, Rearview Material Monitoring Camera, Extension Collars, Spill Guard Kit, Central Point Grease Kit (S400C only), Ratchet Tie-Down Kit, Chain Tie-Down Kit, Vibrator, LED Work Light Kit, LED Strobe Light Kit, Rolled Tarp Kit, Feed Gate (S400C)	ACCESSORIES	Tri-Shield Pre-Wet & Liquid Application System, Rearview Material Monitoring Camera, Extension Collars, Spill Guard Kit, Central Point Grease Kit (S500C only), Ratchet Tie-Down Kit, Chain Tie-Down Kit, Vibrator, LED Work Light Kit, LED Strobe Light Kit, Feed Gate (S500C), Rolled Tarp Kit
VEHICLE COMPATIBILITY	Dump Body or Flatbed Trucks (Over 15,000 lb GVWR)	VEHICLE COMPATIBILITY	Dump Body or Flatbed Trucks (Over 15,000 lb GVWR)	VEHICLE COMPATIBILITY	Dump Body or Flatbed Trucks (Over 15,000 lb GVWR)
MIN. RECOMMENDED BED LENGTH	90"	MIN. RECOMMENDED BED LENGTH	96"	MIN. RECOMMENDED BED LENGTH	96"

* Requires extension collar accessory (#85699 adds 0.5 cu yd to 0.7 cu yd model; #93980 adds 0.5 cu yd for 1.5 & 2.2 cu yd models; #93985 adds 1.0 cu yd for 3.0, 4.0, & 5.0 cu yd models)

** Requires a Truck Upfit Accessory Kit

S = Stainless Steel P = Polyethylene Number = Capacity A = Auger C = Chain

MARAUDER™

POLY HOPPER SPREADERS



1.5 CU YD

P150C | P150A

2.2 CU YD

P220C | P220A

FEATURES	DESCRIPTION	FEATURES	DESCRIPTION
CAPACITY	1.5 cu yd	CAPACITY	2.2 cu yd
CONSTRUCTION	Polyethylene	CONSTRUCTION	Polyethylene
MATERIAL DELIVERY SYSTEM	HELIXX™ Auger Technology features a patented corkscrew material delivery system that is optimized to operate in the target range for rock salt spreading best practices. Pintle Chain Conveyor delivers reliable, smooth, and consistent material flow for heavy, dense materials while reducing bridging.	MATERIAL DELIVERY SYSTEM	HELIXX Auger Technology features a patented corkscrew material delivery system that is optimized to operate in the target range for rock salt spreading best practices. Pintle Chain Conveyor delivers reliable, smooth, and consistent material flow for heavy, dense materials while reducing bridging.
INTERLOCKING LIDS	Standard	INTERLOCKING LIDS	Standard
ACCESSORIES	Tri-Shield Pre-Wet & Liquid Application System, Rearview Material Monitoring Camera, Central Point Grease Kit (P150C only), Vibrator, Inverted V (Accessory for P150C, standard on P150A), LED Work Light Kit, LED Strobe Light Kit, Feed Gate (P150C)	ACCESSORIES	Tri-Shield Pre-Wet & Liquid Application System, Rearview Material Monitoring Camera, Central Point Grease Kit (P150C only), Vibrator, Inverted V (Accessory for P150C, standard on P150A), LED Work Light Kit, LED Strobe Light Kit, Feed Gate (P220)
VEHICLE COMPATIBILITY	3/4- & 1-Ton Pickup Trucks	VEHICLE COMPATIBILITY	3/4- & 1-Ton Pickup Trucks
MIN. RECOMMENDED BED LENGTH	74"	MIN. RECOMMENDED BED LENGTH	90"

S = Stainless Steel P = Polyethylene Number = Capacity A = Auger C = Chain

TRI-SHIELD PRE-WET & DIRECT LIQUID APPLICATION SYSTEM

More jobs can be done even faster with the Tri-Shield Pre-Wet & Direct Liquid Application system. Spread, pre-wet, and spray with one tool that easily attaches to your MARAUDER™ hopper spreader, allowing you to maximize your salt usage and deliver better service.

CONFIGURATION	50 GALLON	200 GALLON	300 GALLON
TANKS	2 @ 25 gallons	4 @ 50 gallons	4 @ 50 gallons 2 @ 50 gallons expansion
VEHICLE COMPATIBILITY	0.7, 1.5, and 2.2 cu yd MARAUDER hopper spreaders	3.0, 4.0 or 5.0 cu yd MARAUDER hopper spreaders	3.0, 4.0 or 5.0 cu yd MARAUDER hopper spreaders
VEHICLE APPLICATIONS	¾ and 1-ton vehicles	Larger flatbed vehicles	Larger flatbed vehicles

“ CONTROL CHOICE.

Take control over your de-icing equipment.

Choose between the Dual Variable Speed Control or the all-new Auto Speed Control.



DUAL VARIABLE-SPEED CONTROL allows you to precisely match material delivery and spread patterns to conditions. Four standard accessory buttons and a dedicated blast button provide in-cab efficiency.



AUTO SPEED CONTROL provides all the benefits of the dual variable-speed control while allowing the operator to set the desired application rate. By directly tying into the vehicle's OBD-II port, the hopper instantly reacts to changes in speed, alerting the operator if they are going too fast or slow to maintain the target application rate. The hopper spinner is stopped automatically if the vehicle exceeds 35 mph or stops. The Auto Speed Control is compatible with WESTERN® hopper spreaders equipped with the FLEET FLEX electrical system.




DIRECT LIQUID APPLICATION & PRE-WET CAPABILITIES

Two nozzles at the base of the chute provide direct liquid application and a drip tube in the pre-wet chamber treats the granular material before it hits the broadcast spinner.



MANUAL CONTROL VALVE

A manual lever on the pump box allows the operator to easily switch between pre-wet or direct liquid application mode when the accessory system is active.



7 GALLONS PER MINUTE

Suitable for either pre-wetting granular material or spraying a direct application, a 12-volt motor and pump combination provide a consistent spray rate for low maintenance and reliable performance.



INTEGRATED CONTROL

Reduce cab clutter and operator proficiency by using the on/off accessory control that is seamlessly integrated into the MARAUDER spreader controls.



TAILGATE SERIES

THE **LOW-PRO 300, 300G, & 300W, PRO-FLO™ 525 & 900 AND LOW PROFILE 500, 1000 & 2500 SPREADERS**

“ CONSIDER THE **JOB DONE.**

When frigid temperatures are in the forecast, your operation has to be ready for a battle with icy conditions. For small properties, touch-up jobs, and sensitive areas, tailgate spreaders are the answer. Easy to fill with a variety of bagged de-icers, tailgate spreaders effortlessly attach with a variety of mount options and leave the bed of your truck free to haul other needed equipment.



CONSERVE SPACE

By mounting the spreader on the tailgate of your truck, the entire truck bed is left free to haul bags of extra de-icing material or additional equipment.



MOUNTING CHOICES*

A wide variety of mounting choices allow you to select the model that best works with your vehicle fleet.



POLYETHYLENE CONSTRUCTION

High-quality polyethylene construction stands up to the cold and corrosive environment of icy conditions. Molded in our Madison Heights, MI facility, Western Products controls the quality of our tubs to ensure performance when it's needed.

*See the Mounts Guide on Page 16 for mount options and compatibility.



LOW-PRO 300 & 300G

POLY TAILGATES

LOW-PRO 300W

WIRELESS POLY TAILGATE

FEATURES	DESCRIPTION	FEATURES	DESCRIPTION
CAPACITY	3.00 cu ft	CAPACITY	3.00 cu ft
CONSTRUCTION	Polyethylene	CONSTRUCTION	Polyethylene
MATERIAL DELIVERY SYSTEM	2.50" x 5.75" Steel Vertical Auger (300 Only)	MATERIAL DELIVERY SYSTEM	2.50" x 5.75" Steel High-Flow Auger
CONTROL	Variable-Speed Control (Included)	CONTROL	Wireless Key Fob
SPREAD WIDTH	Up to 20' (300G) Up to 25' (300)	SPREAD WIDTH	25'
STANDARD FEATURES	Clear Weather Cover (300), Electric Gate (300G), Clear Weather Cover (300G), Vertical Auger (300)	STANDARD FEATURES	Clear Weather Cover
ACCESSORIES	N/A	ACCESSORIES	Wireless Vehicle Harness
INCLUDED MOUNTS	Receiver Hitch Mount	INCLUDED MOUNTS	Receiver Hitch Mount
MOUNTS SOLD SEPARATELY	3-Point Mount, Utility Mount, Drop Utility Mount	MOUNTS SOLD SEPARATELY	3-Point Mount, Utility Mount, Drop Utility Mount
MATERIAL COMPATIBILITY	Bagged Rock Salt (300) Bagged Ice Melters, Calcium Flakes, Calcium Chloride Pellets & Bagged Rock Salt (300G)	MATERIAL COMPATIBILITY	Bagged Rock Salt



PRO-FLO™ 525 & 900

POLY TAILGATES

FEATURES	DESCRIPTION
CAPACITY	5.25 cu ft & 9.00 cu ft
CONSTRUCTION	Polyethylene
MATERIAL DELIVERY SYSTEM	3" x 14" Heavy-Duty Steel Horizontal Auger (525) 3" x 20" Heavy-Duty Steel Horizontal Auger (900)
CONTROL	Dual Variable-Speed Control (Included)
SPREAD WIDTH	30' (525) 40' (900)
STANDARD FEATURES	Inverted-V & Vibrator; Molded Lid & Top Screen
ACCESSORIES	Material Control Tube, Work Light
INCLUDED MOUNTS	Combined 3-Point & Receiver Hitch (525)
MOUNTS SOLD SEPARATELY	Universal Pivot Mount, 3-Point Mount, 2" Receiver Mount and Adapter (900)
MATERIAL COMPATIBILITY	Bulk Salt & Fine Materials**



LOW PROFILE 500, 1000 & 2500

POLY TAILGATES

FEATURES	DESCRIPTION
CAPACITY	5.00 cu ft, 8.00 cu ft & 8.50 cu ft
CONSTRUCTION	Polyethylene
MATERIAL DELIVERY SYSTEM	2.63" x 6" Steel Vertical Auger (500 & 1000) 2.63" x 9" Steel Vertical Auger (2500)
CONTROL OPTIONS	Basic On/Off Control (Sold Separately) Variable-Speed Control (Sold Separately)
SPREAD WIDTH	30'
STANDARD FEATURES	Adjustable Feedgate, Adjustable Deflector (2500), Ratchet Straps (500 & 2500), Molded Lid
ACCESSORIES	Top Screen & Bag Splitter (500 & 2500), Top Screen (1000), 5-Flight Auger (All), Adjustable Deflector (500 & 1000), Truck Protector Flap (1000)
INCLUDED MOUNTS	2" Receiver Hitch (500 & 2500)
MOUNTS SOLD SEPARATELY	2" Receiver & 3-Point Adapter (1000) and Receiver Mount (1000), SWING AWAY® Mount, Fixed Mount (1000)
MATERIAL COMPATIBILITY	Bagged Ice Melters, Bagged Rock Salt, Calcium Flakes* & Calcium Chloride Pellets*

*May require 5-flight Auger Accessory to work with finer materials

**May require Material Control Tube to work with finer materials

MOUNT & MATERIAL COMPATIBILITY

MOUNTS GUIDE

	LOW-PRO 300	LOW-PRO 300G	LOW-PRO 300W	PRO-FLO™ 525	PRO-FLO™ 900	LOW PROFILE 500	LOW PROFILE 1000	LOW PROFILE 2500
TAILGATE SPREADER MOUNTS								
RECEIVER HITCH MOUNT	std	std	std	std	x*	std	x*	std
2" RECEIVER HITCH						std	x	std
FIXED MOUNT							x	
SWING AWAY® MOUNT							x	
UTILITY MOUNT	x	x	x					
DROP UTILITY MOUNT	x	x	x					
3-POINT MOUNT	x	x	x	std	x			
UNIVERSAL PIVOT MOUNT					x			

*Requires additional adapter
std = Included standard with spreader
x = Sold separately

MATERIAL DROP GUIDE

	MARAUDER™	LOW-PRO 300	LOW-PRO 300G	LOW-PRO 300W	PRO-FLO 525	PRO-FLO 900	LOW PROFILE 500	LOW PROFILE 1000	LOW PROFILE 2500
MATERIAL TYPE	HOPPERS	TAILGATES							
BAGGED ICE MELTERS		x		x	x	x	x	x	x
BAGGED ROCK SALT		x		x	x	x	x	x	x
BULK SALT	x				x	x			
CALCIUM FLAKES			x		x	x	x†	x†	x†
CALCIUM CHLORIDE PELLETS			x		x	x	x†	x†	x†
50/50 SALT/SAND MIX	x								
SAND	x								

NOTE: Assumes Dry, Free-Flowing Materials
 *May require use of material control tube accessory.
 †May require 5-flight auger accessory.

	WB-100B	WB-160D
MATERIAL TYPE	WALK-BEHINDS	
BAGGED ICE MELTERS	x	x
BAGGED ROCK SALT	x	x
BULK SALT		
CALCIUM FLAKES	x	x
CALCIUM CHLORIDE PELLETS	x	x
50/50 SALT/SAND MIX		
SAND		

	SS-120 SPRAYER	PRE-WET SYSTEM
MATERIAL TYPE	WALK-BEHIND	ACCESSORY
BRINE	x	x
CALCIUM CHLORIDE SOLUTION	x	x
PREMIUM SOLUTIONS	x	x

Selecting the proper de-icing materials can vary by operator preference, experience and environmental considerations.
 Consult your local WESTERN® dealer with questions regarding material selection and availability.

SPECIFICATIONS

MARAUDER™ Stainless Steel



SPREADER TYPE	HOPPER		HOPPER		HOPPER		HOPPER	
MODEL	S035C / S035A	S070C / S070A	S150C / S150A	S220C / S220A	S300C / S300A	S400C / S400A	S500C / S500A	
BODY SIDE LENGTH	30" (0.76 cu m)	54" (1.37 m)	84" (2.13 m)	96" (2.44 m)	96" (2.44 m)	108" (2.74 m)	108" (2.74 m)	
CAPACITY (VOLUME)	0.35 cu yd (0.27 cu m)	0.7 cu yd (0.54 cu m)	1.5 cu yd (1.15 cu m)	2.2 cu yd (1.68 cu m)	3.0 cu yd (2.29 cu m)	4.0 cu yd (3.06 cu m)	5.0 cu yd (3.82 cu m)	
CAPACITY (WEIGHT)	750 lb (340.2 kg)	1,500 lb (680.39 kg)	3,240 lb (1,470 kg)	4,752 lb (2,155 kg)	6,480 lb (2,939 kg)	8,640 lb (3,919 kg)	10,800 lb (4,899 kg)	
HOPPER CONSTRUCTION	Riveted 16 Gauge Stainless Steel	Riveted 16 Gauge Stainless Steel	Riveted 16 Gauge Stainless Steel	Riveted 16 Gauge Stainless Steel	Riveted 16 Gauge Stainless Steel	Riveted 16 Gauge Stainless Steel	Riveted 16 Gauge Stainless Steel	
HOPPER DIMENSIONS	Chain: 30" x 38" x 26" (0.76 m x 0.97 m x 0.66 m) Auger: 30" x 38" x 25.75" (0.76 m x 0.97 m x 0.65m)	Chain: 54" x 43" x 28" (2.06 m x 1.09 m x 1.17 m) Auger: 54.5" x 42.75" x 27.25" (2.06 m x 1.09 m x 1.14 m)	84.5" x 50" x 32" (2.14 m x 1.27 m x 0.81 m)	96.5" x 50" x 35.75" (2.45 m x 1.27 m x 0.91 m)	96.5" x 70" x 41" (2.45 m x 1.78 m x 1.04 m)	108.5" x 70" x 43.75" (2.76 m x 1.78 m x 1.11 m)	108.5" x 70" x 50.50" (2.76 m x 1.78 m x 1.28 m)	
DIMENSIONS OVERALL	Chain: 57" x 38" x 46" (1.45 m x 0.97 m x 1.17 m) Auger: 52.75" x 38" x 45.5" (1.34 m x 0.97 m x 1.16 m)	Chain: 81" x 43" x 46" (1.37 m x 1.09 m x 0.71 m) Auger: 81" x 42.75" x 45" (1.38 m x 1.09 m x 1.14 m)	Chain: 107" x 50" x 51.75" (2.71 m x 1.27 m x 1.31 m) Auger: 111.5" x 50" x 50.5" (2.83 m x 1.27 m x 1.28 m)	Chain: 119.25" x 50" x 55.50" (3.03 m x 1.27 m x 1.41 m) Auger: 123" x 50" x 50.5" (3.12 m x 1.78 m x 1.82 m)	Chain: 120.25" x 70" x 72.75" (3.05 m x 1.78 m x 1.85 m) Auger: 123" x 70" x 71.50" (3.12 m x 1.78 m x 1.82 m)	Chain: 128.75" x 70" x 75.50" (3.27 m x 1.78 m x 1.92 m) Auger: 129" x 70" x 74.25" (3.28 m x 1.78 m x 1.89 m)	Chain: 126.25" x 70" x 82.25" (3.21 m x 1.78 m x 2.09 m) Auger: 129" x 70" x 81" (3.28 m x 1.78 m x 2.06 m)	
MIN. BED LENGTH	30" (0.76 m)	44" (1.1 m)	76" (1.93 m)	90" (2.29 m)	90" (2.29 m)	96" (2.44 m)	96" (2.44 m)	
APPROX. WEIGHT (EMPTY)*	Chain: 235 lb (106.59) Auger: 192 lb (87.1 kg)	Chain: 420 lb (190.51 kg) Auger: 337 lb (152.9 kg)	Chain: 530 lb (240 kg) Auger: 500 lb (227 kg)	Chain: 580 lb (263 kg) Auger: 550 lb (249 kg)	Chain: 750 lb (340 kg) Auger: 700 lb (318 kg)	Chain: 820 lb (372 kg) Auger: 770 lb (349 kg)	Chain: 910 lb (413 kg) Auger: 850 lb (386 kg)	
SPINNER SIZE	12" Diameter (30.5 cm)	12" Diameter (30.5 cm)	16" Diameter (40.64 cm)	16" Diameter (40.64 cm)	16" Diameter (40.64 cm)	16" Diameter (40.64 cm)	16" Diameter (40.64 cm)	
SPREADING WIDTH	Salt: Up to 36' (10.97 m) Sand: Up to 24' (7.32 m) (S035C Only)	Up to 30' (9.14 m)	Salt: 36' (10.97 m) Sand: 24' (7.32 m)	Salt: 36' (10.97 m) Sand: 24' (7.32 m)	Salt: 36' (10.97 m) Sand: 24' (7.32 m)	Salt: 36' (10.97 m) Sand: 24' (7.32 m)	Salt: 36' (10.97 m) Sand: 24' (7.32 m)	
VEHICLE COMPATIBILITY	UTVs (S035C/S035A); 1/2, 3/4 or 1-Ton Pick Up Truck**	1/2-Ton & Light Duty Pickup Trucks	3/4- & 1-Ton Pickup Trucks	3/4- & 1-Ton Pickup Trucks	Dump Body or Flat Bed Trucks (Over 15,000 lb GVWR)	Dump Body or Flat Bed Trucks (Over 15,000 lb GVWR)	Dump Body or Flat Bed Trucks (Over 15,000 lb GVWR)	
MATERIAL DELIVERY DIMENSIONS	Chain: 15.5" Wide (39.37 cm) Auger: 4" Diameter (10.2 cm)	Chain: 15.5" Wide (39.37 cm) Auger: 4" Diameter (10.2 cm)	Chain: 16" Wide (40.64 cm) Auger: 6" Diameter (15.24 cm)	Chain: 16" Wide (40.64 cm) Auger: 6" Diameter (15.24 cm)	Chain: 16" Wide (40.64 cm) Auger: 6" Diameter (15.24 cm)	Chain: 16" Wide (40.64 cm) Auger: 6" Diameter (15.24 cm)	Chain: 16" Wide (40.64 cm) Auger: 6" Diameter (15.24 cm)	

MARAUDER™ Poly

SPREADER TYPE	HOPPER		HOPPER	
MODEL	P150C P150A		P220C P220A	
BODY SIDE LENGTH	84" (2.13 m)		96" (2.44 m)	
CAPACITY (VOLUME)	1.5 cu yd (1.15 cu m)		2.2 cu yd (1.68 cu m)	
CAPACITY (WEIGHT)	3,240 lb (1,469.9 kg)		4,752 lb (2,155 kg)	
HOPPER CONSTRUCTION	Polyethylene		Polyethylene	
HOPPER DIMENSIONS	96.50" x 63.50" x 46" (2.45 m x 1.61 m x 1.17 m)		104.50" x 63.50" x 51.50" (2.65 m x 1.61 m x 1.31 m)	
DIMENSIONS OVERALL	108.25" x 63.50" x 51.75" (2.75 m x 1.61 m x 1.31 m)		116.25" x 63.50" x 55.50" (2.95 m x 1.61 m x 1.41 m)	
MIN. BED LENGTH	74" (1.88 m)		90" (2.29 m)	
APPROX. WEIGHT (EMPTY)*	Chain: 723 lb (328 kg) Auger: 673 lb (305.3 kg)		Chain: 823 lb (373.3 kg) Auger: 793 lb (360 kg)	
SPINNER SIZE	16" Diameter (40.64 cm)		16" Diameter (40.64 cm)	
SPREADING WIDTH	Salt: 36' (10.97 m) Sand: 24' (7.32 m)		Salt: 36' (10.97 m) Sand: 24' (7.32 m)	
VEHICLE COMPATIBILITY	3/4- & 1-Ton Pickup Trucks		3/4- & 1-Ton Pickup Trucks	
MATERIAL DELIVERY DIMENSIONS	Chain: 16" Wide (40.64 cm) Auger: 6" Diameter (15.24 cm)		Chain: 16" Wide (40.64 cm) Auger: 6" Diameter (15.24 cm)	



** Requires a Truck Upfit Accessory Kit

SPECIFICATIONS



LOW-PRO 300W

SPREADER TYPE	TAILGATE
MODEL	300W
CAPACITY	3.00 cu ft (0.09 cu m)
HOPPER CONSTRUCTION	Polyethylene
DIMENSIONS OVERALL	22" x 30" x 32" (55.90 cm x 76.20 cm x 81.30 cm)
APPROX. WEIGHT (EMPTY)	68 lb (30.8 kg) With Mount
MOTOR	Electric, 12V 1/3 hp
AUGER (DIA. x LENGTH)	—
SPINNER SIZE	10" Nylon/Glass Reinforced Resin
SPREADING WIDTH	Up to 25' (7.62 m)
VEHICLE APPLICATION	Tractors, UTVs, SUVs, 1-Ton or Smaller Pickups
AVAILABLE MOUNTS	Standard 2" Receiver, Optional Drop Utility, Utility Mount, 3-Point Mounts



LOW-PRO 300 & 300G

SPREADER TYPE	TAILGATE	TAILGATE
MODEL	300G	300
CAPACITY	3.0 cu ft (0.09 cu m)	3.0 cu ft (0.09 cu m)
HOPPER CONSTRUCTION	Polyethylene	Polyethylene
DIMENSIONS OVERALL	22" x 30" x 30" (55.9 cm x 76.2 cm x 76.2 cm)	22" x 32" x 30" (55.9 cm x 76.2 cm x 81.3 cm)
APPROX. WEIGHT (EMPTY)	75 lb (34.0 kg)	68 lb (30.8 kg)
MOTOR	12-volt DC motor mounted in weather-resistant enclosure	12-volt DC motor mounted in weather-resistant enclosure
AUGER (DIA. x LENGTH)	—	3' Vertical High-Flow Auger
SPINNER SIZE	10" Nylon/Glass Reinforced Resin	10" Nylon/Glass Reinforced Resin
SPREADING WIDTH	Up to 20' (6.1 m)	Up to 25' (7.6 m)
VEHICLE APPLICATION	UTVs, Tractors, 1-Ton or Smaller Pickups	UTVs, Tractors, 1-Ton or Smaller Pickups
AVAILABLE MOUNTS	Standard 2" Receiver Hitch, Optional 3-Point Mount, Utility Mount, Drop Utility Mount	

PRO-FLO™ 525 & 900



SPREADER TYPE	TAILGATE	TAILGATE
MODEL	525	900
CAPACITY	5.25 cu ft (0.15 cu m)	9.00 cu ft (0.25 cu m)
HOPPER CONSTRUCTION	Polyethylene	Polyethylene
DIMENSIONS OVERALL	20.50" x 38" x 34" (52.10 cm x 96.50 cm x 86.40 cm)	24" x 52" x 36" (60.90 cm x 132.10 cm x 91.40 cm)
APPROX. WEIGHT (EMPTY)	160 lb with mount (72.60 kg)	180 lb w/o mount* (81.70 kg)
MOTOR	Dual Electric, 12V, 1/3 hp	Dual Electric, 12V, 1/3 hp
AUGER (DIA. x LENGTH)	3" x 14" Heavy-Duty Solid Steel (7.26 cm x 35.56 cm)	3" x 20" Heavy-Duty Solid Steel (7.26 cm x 50.80 cm)
SPINNER SIZE	10" (25.40 cm)	12" (30.50 cm)
SPREADING WIDTH	Up to 30' (9.14 m)	Up to 40' (12.19 m)
VEHICLE APPLICATION	Tractors, UTVs, SUVs, 1-Ton or Smaller Pickups	Tractors, 1-Ton or Smaller Pickups
AVAILABLE MOUNTS	Standard Combined 3-Point & Receiver Hitch	Optional Universal Pivot Mount, Receiver Mount (required adapter kit), 3-Point Mount

LOW PROFILE 500, 1000 & 2500



SPREADER TYPE	TAILGATE	TAILGATE	TAILGATE
MODEL	500	1000	2500
CAPACITY	5.00 cu ft (0.14 cu m)	8.00 cu ft (0.23 cu m)	8.50 cu ft (0.24 cu m)
HOPPER CONSTRUCTION	Polyethylene	Polyethylene	Polyethylene
DIMENSIONS OVERALL	21" x 39" x 34" (53.34 cm x 99.06 cm x 86.40 cm)	19.50" x 50.50" x 35" (49.53 cm x 128.27 cm x 88.90 cm)	25" x 50" x 42" (63.50 cm x 127.00 cm x 106.68 cm)
APPROX. WEIGHT (EMPTY)	75 lb with mount (34.00 kg)	105 lb w/o mount* (47.00 kg)	131 lb with mount (59.40 kg)
MOTOR	Electric, 12V, 1/3 hp	Electric, 12V, 1/3 hp	Electric, 12V, 1/3 hp
AUGER (DIA. x LENGTH)	2.63" x 6" (6.68 cm x 15.24 cm)	2.63" x 6" (6.68 cm x 15.24 cm)	2.63" x 9" (6.68 cm x 22.86 cm)
SPINNER SIZE	10" (25.40 cm)	10" (25.40 cm)	15" (38.10 cm)
SPREADING WIDTH	Up to 30' (9.14 m)	Up to 30' (9.14 m)	Up to 30' (9.14 m)
VEHICLE APPLICATION	Vehicles with Class III Hitch	Full-Size Trucks (over 6,000 lb GVWR)	Full-Size Trucks (over 6,000 lb GVWR)
AVAILABLE MOUNTS	Standard Class III 2" Receiver Hitch Mount	Optional 2" Receiver Mount & 3-Point Adapter, SWING AWAY® Mount, Fixed Mount	Standard Class IV Receiver Hitch Mount

* Mounts sold separately

**WB-160D****WB-100B**

SPREADER TYPE	WALK-BEHIND	WALK-BEHIND
CAPACITY	160 lb (72.00 kg)	100 lb (45.00 kg)
HOPPER CONSTRUCTION	Polyethylene	Polyethylene
DIMENSIONS OVERALL	48" x 38.25" x 36" (121.92 cm x 97.16 cm x 91.44 cm)	50" x 26" x 28" (127 cm x 66.04 cm x 71.12 cm)
APPROX. WEIGHT (EMPTY)	55 lb (24.00 kg)	25 lb (11.00 kg)
SPINNER SIZE	—	10" (25.40 cm)
SPREADING WIDTH	Up to 3' (0.91 m)	Up to 20' (6.00 m)

**SS-120**

SPREADER TYPE	WALK-BEHIND
EMPTY WEIGHT	60 lb (27.20 kg)
DIMENSIONS OVERALL	48" x 28" x 33" (122.00 cm x 71.00 cm x 84.00 cm)
CAPACITY	12 gal (45.40 L)
SPRAYING WIDTH	Up to 48" (122.00 cm)
SPRAYING VOLUME	1 gal/min (3.80 L/min)
FRAME	Powder Coated Steel
TANK	One-Piece LLDPE
MOTORS	12-Volt, Direct-Drive Pump



STORAGE CONTAINERS

	STORAGE	STORAGE	STORAGE	STORAGE
MODEL NUMBER	74069	74071	74073	74075
MATERIAL CAPACITY	3 cu ft	6 cu ft	12 cu ft	18 cu ft
EMPTY WEIGHT	19 lb (8.62 kg)	35.5 lb (16.10 kg)	50.5 lb (22.91 kg)	58 lb (26.31 kg)
OVERALL LENGTH	33" (83.82 cm)	48" (121.92 cm)	48" (121.92 cm)	48" (121.92 cm)
OVERALL WIDTH	22.75" (57.79 cm)	33.25" (84.46 cm)	33.25" (84.46 cm)	33.25" (84.46 cm)
OVERALL HEIGHT	17.4" (44.20 cm)	20.75" (52.71 cm)	27.75" (70.49 cm)	35.75" (90.81 cm)
FORK POCKETS	No	Yes	Yes	Yes

WEBSITE RESOURCES

FIND THE SPREADERS THAT BEST FIT YOUR FLEET

Much like the variety of spreading materials on the market, there are countless spreader options available. Western Products manufactures a full line of spreaders from walk-behind spreaders to bed-mounted and dump box spreaders. Find the WESTERN® spreaders that will help you get more jobs done faster at westernplows.com/spreader-selector.

YOUR LOCAL WESTERN DEALER IS HERE TO HELP

Call or visit your local WESTERN dealer to learn more about Western Products' full-line of professional-grade snowplows and spreaders, to inquire about product availability or installation, or ask any questions about which products would be the best fit for your job or vehicle applications. Find your local WESTERN dealer by visiting westernplows.com/dealers.

WARRANTY & REGISTRATION

Western Products offers a 2-year limited warranty on most WESTERN snow and ice control products. Register your equipment today to create a record of your purchase and receive a full range of benefits including trouble-free warranty work, serial number identification for theft protection, and promotions. Register your products by visiting westernplows.com/warranty.

Specifications subject to change without prior notice. Please visit westernplows.com for the most current specifications.

ACCESSORIES



PROTECT YOUR INVESTMENT WITH WESTERN® PARTS & ACCESSORIES

Ensure your WESTERN equipment remains efficient and reliable season after season with Factory Original parts and accessories from your local WESTERN dealer. Using “will-fit” alternatives can alter your spreader’s performance and may affect your product warranty. Stick with the WESTERN brand for the parts and accessories you need. It’s the smart choice for maximizing the return on your investment.



TRI-SHIELD PRE-WET & DIRECT LIQUID APPLICATION

Activates de-icing material by applying a liquid de-icing agent directly to the material prior to it hitting the spinner, and sprays liquid brine directly onto pavement.



SPILL GUARD KIT

Provides loader with improved line of sight and prevents material overflow from off-center loading. Includes prepunched holes for addition of side extensions.



LED WORK LIGHT KIT

For better visibility at the rear of the spreader at night.



CONTROL CUP HOLDER MOUNT

Secures your controls on a flexible gooseneck mount for optimal, customizable positioning.



SPREADER CONTROL ADAPTER PLATE

Gain the flexibility and easy installation benefits of the cup holder control mount (not included).



REARVIEW MATERIAL MONITORING CAMERA

View your material input from the comfort of your cab to ensure a smooth spread pattern and optimal material output.

Consult your local WESTERN dealer or westernplows.com for accessory compatibility or availability.

TAILGATE ACCESSORIES

	LOW-PRO 300	LOW-PRO 300G	LOW-PRO 300W	PRO-FLO™ 525	PRO-FLO™ 900	LOW PROFILE 500	LOW PROFILE 1000	LOW PROFILE 2500
5-FLIGHT AUGER		std				x	x	x
ADJUSTABLE DEFLECTOR	std			std	std	x	x	
WORK LIGHT KIT				x	x	x	x	x
SECONDARY WORK LIGHT KIT				x	x		x	x
TOP SCREEN						x	x	x
SPREADER CONTROL ADAPTER PLATE				x	x			
CONTROL CUP HOLDER MOUNT				x	x			
TRUCK PROTECTOR FLAP							x	
WIRELESS VEHICLE HARNESS			x					
MATERIAL CONTROL TUBE				x	x			
UTV SPREADER CONTROL SHIELD				x	x			

CHAIN ACCESSORIES

	S035C	S070C	S150C	P150C	S220C	P220C	S300C	S400C	S500C
INVERTED V	x	x	x	x	x	x	std	std	std
CHUTE EXTENSION KIT	x		x	x	std	std	std	std	std
EXPANSION COLLAR	x	x	x		x		x	x	x
SPILL GUARDS	x	x	x		x		x	x	x
FEEDGATE KIT			x		x		x	x	x
REARVIEW MATERIAL MONITORING CAMERA		x	x	x	x	x	x	x	x
PULLOVER TARP KIT	x	x	x		x				
ROLLED TARP COVER							x	x	x
CENTRAL POINT GREASE KIT		x	x	x	x	x	x	x	x
VIBRATOR KIT	x	x	x	x	x	x	x	x	x
STROBE LIGHT KIT	x	x	x	x	x	x	x	x	x
LICENSE PLATE KIT	x								
WORK LIGHT KIT	x	x	x	x	x	x	x	x	x
SECONDARY WORK LIGHT KIT	x	x	x	x	x	x	x	x	x
RATCHET TIE-DOWN KIT	x								
TRUCK UPFIT KIT	x								
VEHICLE-SIDE HARNESS KIT	x	x							

AUGER ACCESSORIES

	S035A	S070A	S150A	P150A	S220A	P220A	S300A	S400A	S500A
INVERTED V	x	x	std	std	std	std	std	std	std
CHUTE EXTENSION KIT	x		x	x	std	std	std	std	std
EXPANSION COLLAR	x	x	x		x		x	x	x
SPILL GUARDS	x	x	x		x		x	x	x
REARVIEW MATERIAL MONITORING CAMERA	x	x	x	x	x	x	x	x	x
PULLOVER TARP KIT	x	x							
ROLLED TARP COVER			x		x		x	x	x
VIBRATOR KIT	x	x	x	x	x	x	x	x	x
STROBE LIGHT KIT	x	x	x	x	x	x	x	x	x
LICENSE PLATE KIT	x	x							
WORK LIGHT KIT	x	x	x	x	x	x	x	x	x
SECONDARY WORK LIGHT KIT	x	x	x	x	x	x	x	x	x
RATCHET TIE-DOWN KIT	x								
TRUCK UPFIT KIT	x								
VEHICLE-SIDE HARNESS KIT	x								

* Material weight equates to approximately 2,160 lb/cu yd or 80 lb/cu ft for 1 bag of rock salt.

std = Included standard with spreader
x = Sold separately

LEAVE NO JOB UNFINISHED.

WB-100B / WB-160D WALK-BEHINDS

WESTERN® walk-behind spreaders deliver professional, hassle-free performance. Constructed of sturdy, corrosion-free polyethylene, both the broadcast spreader and the drop spreader can handle most ice-melt materials. With pneumatic tires and a powder coated steel frame, these spreaders are built to stand up to the demands of commercial use.

WB-100B BROADCAST SPREADER

The WB-100B poly broadcast spreader is ideal for wider areas, such as driveways, courtyards, and wide walkways. 100 lb capacity.

WB-160D DROP-STYLE SPREADER

The WB-160D poly drop-style spreader is perfect for narrow walkways and keeping material out of adjacent landscape features. 160 lb capacity.



STANDARD FEATURES

- Clear Hopper Cover
- Powder Coated Steel Frame
- 13" Pneumatic Tires
- Top Screen
- 10" Molded Spinner*

*On WB-100B only.

STOP ICE IN YOUR TRACKS.

SS-120 SIDEWALK SPRAYER

Apply liquid anti-icing before the storm to help prevent snow and ice from forming a bond with the pavement, so it's easier to scrape clean down to the surface. The SS-120 walk-behind sidewalk sprayer helps you do just that. Spray anti-icing liquid before the storm and your sidewalks will come out cleaner than ever.



CAPACITY

12-gallon poly tank with easy-fill cap.

BATTERY-POWERED ELECTRIC PUMP

12-volt electric pump sprays up to one gallon per minute at 60 psi.

RECHARGEABLE BATTERY

Battery powers up to ten full tanks (120 gal) with a single charge.

HEIGHT-ADJUSTABLE NOZZLE

The height-adjustable nozzle sprays up to four feet wide.

CONVENIENT SPRAY WAND

Use the convenient spray wand with 8' coil hose to treat stairs, entryways, and other hard-to-reach places. Features a spray distance of 15'.

OVERSIZE TIRES

Large 13" pneumatic tires enhance maneuverability over ice and snow.

BRING ON-SITE STORAGE CLOSE TO THE ACTION.

STORAGE CONTAINERS

Increase the efficiency of your crews by bringing the storage of supplies, tools, and PPE closer to where they are used. Western Products helps the work get done faster with a full line of durable, weather resistant, polyethylene storage containers. Four sizes—3, 6, 12, and 18 cu ft—are available to fit your storage footprint. Molded-in fork pockets on the 6, 12, and 18 cu ft models allow for easy placement, even when fully loaded, exactly where storage is needed. To protect the contents, each storage container has a molded-in closure that can be secured with an extended shank padlock.

These versatile containers can be used for a variety of storage applications:

- Rock Salt for Winter Cleanup and Self-Servicing
- PPE and Oil Dry for Shops and Maintenance Centers
- Bulk Item Storage for Shops, Maintenance, and Work Centers

CAPACITY

The number of 50-lb bags of rock salt that can be stored in each container:

- 3 cu ft = 4 bags
- 6 cu ft = 9 bags
- 12 cu ft = 19 bags
- 18 cu ft = 28 bags



Western Products offers a limited warranty of one year on storage containers.



“





Western Products | P.O. Box 245038 | Milwaukee, WI 53224-9538



westernplows.com

Western Products reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Western Products or the vehicle manufacturer may require or recommend optional equipment for spreaders. Do not exceed vehicle ratings with a spreader. This product is manufactured under the following US patents: 7,347,390; 7,481,384 7,540,436; 9,033,265; 9,296,571; 9,757,744; 11,680,379; and other patents pending. Western Products offers a limited warranty for all spreaders. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: HELIXX™, MARAUDER™, MVP PLUS™, PRO-FLO™, SWING AWAY®, WESTERN®, WIDE-OUT™.

©2026 Douglas Dynamics, LLC
All rights reserved.

 A DIVISION OF DOUGLAS DYNAMICS, LLC

Printed in U.S.A.
Form No. 32595 – JULY26

